

• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an ection every 12 months and after any exceptional event in the life of the product

• PPE inspection should be conducted with the manufacturer's Instructions for Use.

Download the instructions at $\underline{\mathsf{PETZL}.\mathsf{COM}}$.

SPORT HARNESSES

User information PPE information Surname Model Address Serial number Year of manufacture Date of purchase Identifier Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France

Q **⊗**▶ ति N/A Good condition (G) To monitor (TM) To repair (TR) Do not use, retire (R) Not applicable

1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):



2. Preliminary observations

- Verify the presence and legibility of the serial number and the CE mark.
- Verify that the product lifetime has not been exceeded.
- Compare with a new device to verify there are no modifications or missing elements.

3. Checking the condition of the straps

- Check for cuts, swelling, damage and wear due to use, to heat, and to contact with chemicals. Check the waistbelt straps, waistbelt bias
- tapes, and leg and shoulder straps if any. Be sure to check any areas hidden by buckles or protectors.

 Check the condition of all safety stitching on both sides. Look for any threads that are loose, worn, or cut. Safety stitching is identified by thread of a different color than that of the webbing.

4. Checking the tie-in points and belay loop

- Check the condition of the belay loop Look for cuts, swelling, damage and wear due to use, to heat, and to contact with chemicals
- · Check the condition of the protective webbing on the tie-in points. Look for cuts, swelling, damage and wear due to use, to heat, and to contact with chemicals.

If the protective webbing on the tie-in points shows signs of wear (holes, cut threads, frayed webbing), retire your harness. Certain harnesses (e.g. SIMBA, LUNA, SELENA, ADJAMA, SAMA) have a red wear indicator on the lower tie-in point. Retire your harness if this indicator is visible.

Verify that the screws on the gated attachment point are present and properly tightened.

Verify the absence of deformation, cracks, marks, wear, corrosion.

5. Checking the condition of the adjustment buckles

- See your harness' Instructions for Use
- Check the condition of the adjustment buckles (marks, cracks, wear, deformation, corrosion...).
- Check that the straps are correctly threaded, with no twists.
- Verify that the buckles operate properly.

6. Special case for FLY harness

- · Verify the knots are present and check the condition of the cord.
- Look for cuts, swelling, damage and wear due to use, to heat, and to contact with chemicals.
- Verify that the toggle and the waistbelt elastic band are working properly.

7. Checking the comfort parts

- Check the condition of the waist and leg foams (cuts, wear, tears...).
- Check the condition of the elastic keepers and leg loop elastics (cuts, wear, tears...).
- Check the condition of the equipment loops (cuts, wear, tears...).

VERDICT	
	Product fit to remain in service
	Product unfit to remain in service

Inspected by	
Company	
Date	Next inspection date